

## AMENDMENT(S) TO THE CLAIMS

1. (Original) A sprinkler, comprising:  
an outer housing having a lower end connectable to a source of pressurized water;  
a riser vertically reciprocable along a vertical axis within the outer housing between  
extended and retracted positions when the source of pressurized water is turned ON and OFF;  
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;  
a turbine mounted inside the riser for rotation about a horizontal axis; and  
a drive mechanism connecting the turbine to the nozzle so that when the source of  
pressurized water is turned ON the resulting rotation of the turbine by the pressurized water  
will rotate the nozzle.

2. (Original) The sprinkler of Claim 1 wherein the drive mechanism includes a  
reversing mechanism for causing the nozzle to rotate between a pair of arc limits.

3. (Currently Amended) The sprinkler of Claim 1 and further comprising a  
mechanism that allows a least one of the arc limits to be adjusted.

4. (Once Amended) The sprinkler of Claim 1 wherein the turbine includes a disk  
and a plurality of equally circumferentially spaced cups formed on the periphery of the disk.

5. (Original) The sprinkler of Claim 1 wherein the turbine and a drive mechanism  
that connects the turbine to the nozzle are mounted inside a pair of clam-shell case members  
inside the riser.

6. (Original) The sprinkler of Claim 5 wherein the drive mechanism includes a  
gear train reduction including a plurality of gears that rotate about a plurality of corresponding  
horizontal axes.

7. (Original) The sprinkler of Claim 5 wherein at least one of the case members  
defines a water inlet.

8. (Original) The sprinkler of Claim 1 and further comprising a manually adjustable stator for varying a rotational speed of the turbine.

9. (Original) The sprinkler of Claim 1 and further comprising a first filter for straining all water flowing into the lower end of the outer housing and a second filter for straining a portion of the water flowing past the turbine.

10. (Original) The sprinkler of Claim 5 wherein the drive mechanism includes a reversing mechanism mounted inside the claim-shell case members that causes the nozzle to rotate between a pair of arc limits.

11. (Currently Amended) A sprinkler, comprising:  
an outer housing having a lower end connectable to a source of pressurized water;  
a riser vertically reciprocable along a vertical axis within the outer housing between extended and retracted positions when the source of pressurized water is turned ON and OFF;  
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;  
a plurality of mating case members dimensioned to fit inside the riser;  
a turbine entirely mounted inside the case members; and  
a drive mechanism including a reversing mechanism and an over-center mechanism that shifts the reversing mechanism, the drive mechanism being mounted inside the case members that connects the turbine to the nozzle so that when the source of pressurized water is turned ON the resulting rotation of the turbine by the pressurized water will rotate the nozzle between a pair of arc limits.

12. Canceled

13. (Original) The sprinkler of Claim 11 and further comprising a mechanism that allows a least one of the arc limits to be adjusted.

14. (Once Amended) The sprinkler of Claim 11 wherein the turbine includes a disk and a plurality of equally circumferentially spaced cups formed on the periphery of the disk.

15. (Original) The sprinkler of Claim 11 wherein the turbine rotates about a horizontal axis.

16. (Original) The sprinkler of Claim 11 wherein the drive mechanism includes a gear train reduction including a plurality of gears that rotate about a plurality of corresponding horizontal axes.

17. (Original) The sprinkler of Claim 11 wherein at least one of the case members defines a water inlet.

18. Canceled

19. (Original) The sprinkler of Claim 11 and further comprising a first filter for straining all water flowing into the lower end of the outer housing and a second filter for straining a portion of the water flowing past the turbine.

20. (Original) A sprinkler, comprising:  
an outer housing having a lower end connectable to a source of pressurized water;  
a riser vertically reciprocable along a vertical axis within the outer housing between extended and retracted positions when the source of pressurized water is turned ON and OFF;  
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;  
a plurality of mating case members dimensioned to fit inside the riser, at least one of the case members defining a water inlet and a water outlet;  
a turbine mounted inside the case members receiving water passing through the inlet for powered rotation about a first horizontal axis;  
a drive mechanism mounted inside the case members that connects the turbine to the nozzle so that when the source of pressurized water is turned ON the resulting rotation of the turbine by the pressurized water will rotate the nozzle, the drive mechanism including a gear train reduction having a plurality of gears that rotate about a plurality of corresponding second horizontal axes and a reversing mechanism for causing the nozzle to rotate between a pair of arc limits; and

16 a manually adjustable stator for varying a rotational speed of the turbine.

21. (Currently Amended) A sprinkler, comprising:

2 an outer housing having a lower end connectable to a source of pressurized water;  
a riser vertically reciprocable along a vertical axis within the outer housing between  
4 extended and retracted positions when the source of pressurized water is turned ON and OFF;  
a nozzle mounted at an upper end of the riser for rotation about the vertical axis; and  
6 a self-contained drive subassembly mounted inside the riser and including entirely  
enclosing a turbine and a drive mechanism that connects the turbine to the nozzle so that when  
8 the source of pressurized water is turned ON the resulting rotation of the turbine by the  
pressurized water will rotate the nozzle, the drive subassembly including a pair of mating  
10 case members that form opposite halves of a hollow container that encloses the turbine and  
drive mechanism.

22. (Original) The sprinkler of Claim 21 wherein the drive mechanism includes  
2 a reversing mechanism for causing the nozzle to rotate between a pair of arc limits.

23. (Original) The sprinkler of Claim 21 wherein the drive subassembly is  
2 configured so that only a portion of the water flowing into the riser drives the turbine.

24. (Once Amended) The sprinkler of Claim 21 wherein the turbine includes a  
2 disk and a plurality of equally circumferentially spaced cups formed on the periphery of the  
disk.

25. (Original) The sprinkler of Claim 21 wherein the turbine rotates about a  
2 horizontal axis.

26. (Original) The sprinkler of Claim 21 wherein the drive mechanism includes  
2 a gear train reduction including a plurality of gears that rotate about a plurality of  
corresponding horizontal axes.

27. (Original) The sprinkler of Claim 23 and further comprising a first screen for filtering the portion of the water flowing into the riser that drives the turbine, and a second screen for filtering a second portion representing a remainder of the water flowing into the riser, the first screen having a finer mesh size than the second screen.

28-29 Canceled

30. (Currently Amended) The sprinkler of Claim ~~21~~ 22 and further comprising a mechanism that allows a least one of the arc limits to be adjusted.

31. (New) A sprinkler, comprising:  
an outer housing having a lower end connectable to a source of pressurized water;  
a riser vertically reciprocable along a vertical axis within the outer housing between extended and retracted positions when the source of pressurized water is turned ON and OFF;  
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;  
a plurality of mating case members dimensioned to fit inside the riser;  
a turbine entirely mounted inside the case members;  
a drive mechanism mounted inside the case members that connects the turbine to the nozzle so that when the source of pressurized water is turned ON the resulting rotation of the turbine by the pressurized water will rotate the nozzle; and  
a manually adjustable stator for varying a rotational speed of the turbine.

32. (New) A sprinkler, comprising:  
an outer housing having a lower end connectable to a source of pressurized water;  
a riser vertically reciprocable along a vertical axis within the outer housing between extended and retracted positions when the source of pressurized water is turned ON and OFF;  
a nozzle mounted at an upper end of the riser for rotation about the vertical axis;  
a self-contained drive subassembly mounted inside the riser and entirely enclosing a turbine and a drive mechanism that connects the turbine to the nozzle so that when the source of pressurized water is turned ON the resulting rotation of the turbine by the pressurized water will rotate the nozzle; and  
a manually adjustable stator for varying a rotational speed of the turbine.